Easy programming using selection button sequence
Flectronic control and data-recording

Thermostatically controlled forced air-cooling

Each column has individual vend motor

24 V D/C motors

Interchangeable parts

One-piece inner door



Model VI	DI 550-8
----------	----------

Capacities:

 Can
 0,33 I
 544

 PET bottle
 0,50 I
 272

Dimensions and weights:

H x W x D (mm) 1830 x 850 x 940 Weight 335 kg

Performance data:

Refrigeration 0,997 kW
Power supply 230 V / 50 Hz
Max. power consumption 875 W

Control Executive; MDB
Cabinet Zinc coated steel,
powder painted

Standard:

Black cabinet
5 digit display
Safety coin return
Cut out for validator or
alternative payment system
Lock
Choice of neutral front poster

Options:

Cabinet colour on request
Two-line LCD display
Security cash system
Anti-vandalism panel in
selection button area
Safety sliding coin insert
Anti-rain kit IP 34
DEX / UCS interface
Special coded lock
Individual graphics



SandenVendo GmbH I Spangerstrasse 22 I D-40599 Düsseldorf Fon: +49 (0)211-740 39-0 I Fax: +49 (0)211-748 85 41 Web: www.SandenVendo.com I e-Mail: infosvg@sandenvendo.com